


Sat-IF-Distribution-Multiswitch

Cascadable Multiswitch 5 in 8

BKD 55-8 BKD 55-8T
 BKD 55-8ST T=Terr. active

- multiswitch with 4 Sat + terrestrial input to 8 outputs
- latest RF-chipset technology
- integrated amplifier for low insertion loss
- small compact size
- high isolation between polarisations
- return loss < 10 dB (low bit errors)
- integrated pre-emphase for cable loss compensation
- Option: terr. passive / active - switchable
- with integrated power supply
- Made in Germany



Type	BKD 55-8 / BKD 55-8T		BKD 55-8 ST switchable			
Feature	Cascadable switch, for Quattro LNB, terr. passive / active					
User outputs	8		8			
Inputs	1 x terr.	4 x Sat	1 x terr.	4 x Sat		
Frequency range	5-862 MHz	950-2150 MHz	5-862 MHz	950-2150 MHz		
Insertion loss (Terr. passive/active)	19 dB / 2 dB	4...1 dB	20 dB / 3 dB	4...1 dB		
Isolation polarisations	30 dB	30 dB	30 dB	30 dB		
Subscriber decoupling	25 dB	25 dB	25 dB	25 dB		
Max. output level passive / active	passive /80 dB μ V ²	102 dB μ V *	passive / 95 dB μ V ²	102 dB μ V *		
Input control signals	12-14,5 V / 16-19 V - 0 /22kHz					
Current consumption / subscriber	38 mA					
Max. total remote feed current	500 mA					
Current consumption	10 mA / 50 mA		20 mA / 60 mA			
Secondary voltage	18 V					
Permissible input voltage range	90-265 V					
Ambient temperature range	-20 bis +55°C					
Dimensions	136 x 136 x 36 mm					
Weight	400 g					

* Terr. EN50083-5, 60-dBKMA, SAT EN50083-3, 35-dB-IMA, ² terr. Active

Änderungen vorbehalten! / Subjects to change without notification!