

Application

Blankom's thinnest profile audio hook-up wire. Amazingly flexible, with 100% foil shield, drain wire and PVC jacket that strips easily for rapid assembly. Suitable for large cable harness bundles, mixing consoles, tape machines and inner-rack wiring.

**Construction****Conductor**

24AWG stranded (7x32), tinned copper,

Insulation

PE – Polyethylene(2YI1).

One pair,

Pair color code

Black&Red

Overall Shield

Aluminum foil + 24AWG Drain wire

Sheath

PVC- black.

Dia. 3,20mm.Ø

Ratings

Flame resistance IEC 60332-1-2,

Operating temperature range

-20°C to +70°C,

Electrical Characteristics**Nom. Characteristic Impedance**

52 Ohms at 1 MHz

Nom. Velocity of Propagation

66%

Nom. Capacitance

C/C 75 pF/mt.

C/S 140 pF/mt.

Nom. DC Resistance

C 85 Ω/km.

S 65 Ω/km.

General Data

Operating voltage.....max.....300 V (RMS)

Marking on.....manufacturer, year and week of
sheath manufacture, designation product
no., according to standart and
length marking.

Delivery length.....on MG 330 drum.....1000 m

Standard color.....Black

Overall diameter.....3.20 mm

Weight.....15 kg/km